



FLOWTECH FP-350 LUBE PUMP (SHOWN OR NOT SHOWN) WITH 3/4\"/>

2-STAGE MANUAL FILTER BASKETS. NOTE: SLURRING RESERVOIR BRINGS COATINGS INTO CONTACT WITH SPRAY BASKETS WHICH BRINGS PARTICULATE FROM BRIGGS AND THEN IS SPRAYED BACK ONTO FOOD PRODUCT IN A RECIRCULATING SYSTEM.

OPERATOR CONTROLS INCLUDE:
 1. VARIABLE UPPER DISC FEED PUMP SPEED
 2. VARIABLE LOWER DISC FEED PUMP SPEED
 3. VARIABLE LOWER SPRAY SPEED
 4. ROTARY ATOMIZERS DIVERT (CONSTANT 1750 RPM)

NOTE:
 BY CONNECTING THE WILEVCO SPRAY APPLICATOR TO OUR CENTRAL RESERVOIR TANK, MIXER & CRYDOLATOR YOU WILL HAVE BATTER CONTROL SYSTEM THAT CONTINUOUSLY MONITORS AND ADJUSTS A BATTERS VISCOSITY AND TEMPERATURE WHILE ALLOWING THE OPERATOR PRECISE CONTROL OF BATTER PICK-UP WEIGHTS.

wilevco

Wilevco, Inc.
 10 Fortune Drive
 Billerica, MA 01821-3996
 Phone: (978) 667-0400
 Fax: (978) 678-3191

THIS DRAWING AND ANY DESIGN HERON IS PATENT PROTECTED. COPYRIGHT AND REMAINS THE PROPERTY OF WILEVCO INC. IT MAY NOT BE COPIED, LOANED OR DISCLOSED TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT. IT IS SUBJECT TO RECALL.

No.	Revision Description	Date	By/Bye
1	0620 PARTS FROM S&E TO PD LUBE (2/16/07) M&S		

RAS2 - 24"
SPRAY APPLICATOR
ASSEMBLY

1 = 1
 01/11/2006
 M & Lablapp
 RAS2-24 - 0626 REV 1 - TEST UNIT