

RTS50, RTS70, RTS100



**Wilevco Reserve Tanks:
Low volume reservoirs
designed for continuous
batter filtering and
distribution between the
Wilevco Batter Mixing
System and batter
applicator(s).**



Compact and ruggedly constructed, the Reserve Tank can be configured with one or more job specific positive displacement pumps incorporating either electric or hydraulic drive. These tanks may also be configured for metering proprietary liquids and/or special ingredients into mixed batter.

FEATURES

- Compact design
- Hydraulic or electric drive
- Operator and maintenance friendly
- Easy clean-up and assembly
- Sanitary construction
- Metering capability
- Interfaces easily with all applicators

APPLICATIONS

- Reserve capacity
- Bypass capability
- Single mixer supplying 2 applicators
- Batter filtration

RTS50, RTS70, RTS100

Technical Specifications

Length: 810 mm • 32 inches
Height: 1270 mm • 50 inches
Width: 480 mm • 19 inches

Shipping Weight:

W/Electric 75 kgs • 165 lbs minimum
W/Hydraulic 57 kg • 125 lbs minimum

Pumps

RTS50 Jabsco	15550-9775	190 L/min (50 GPM)
RTS70 Jabsco	15570-9765	380 L/min (100 GPM)
RTS100 Jabsco	15590-9775	460 L/min (120 GPM)

Electric Motors

RTS50 and 70	TEC 3 phase 1.5 KW (2 HP)
RTS 100	TEFC 3 phase 3.7 KW (5 HP)

Hydraulic Motors

RTS50 and 70	EATON #21308 .0353 L/min/rev 1400 RPM max (.0093 GPM/rev)
RTS 100	TBD

TYPICAL INSTALLATION AND BATTER FLOW

